



1. Features

- n $R_{DS(ON)}=7.2m\Omega$ (typ)@ $V_{GS}=10V$
- n Lead free and green device available
- n Low Rds-on to minimize conductive loss
- n High avalanche current

2. Applications

- n Power supply
- n DC-DC converters

3. Pin configuration



Pin	Function
1	Gate
2	Drain
3	Source

4. Ordering Information

Part Number	Package	Brand
KNB3308B	TO-263	KIA

5. Absolute maximum ratings

Parameter	Symbol	Maximum	Units
Drain-source voltage	V_{DSS}	80	V
Gate-source voltage	V_{GSS}	± 25	V
Continuous drain current	$T_C=25\text{ }^\circ\text{C}$	80	A
	$T_C=100\text{ }^\circ\text{C}$	65	A
Pulse drain current	$T_C=25\text{ }^\circ\text{C}$	I_{DP}^4	320 A
Avalanche current	I_{AS}^5	40	A
Avalanche energy	E_{AS}^5	440	mJ
Maximum power dissipation	$T_C=25\text{ }^\circ\text{C}$	P_D	210 W
	$T_C=100\text{ }^\circ\text{C}$		105 W
Junction & storage temperature range	T_J, T_{STG}	-55~175	$^\circ\text{C}$

6. Thermal characteristics

Parameter	Symbol	Typical	Units
Thermal resistance-junction to case	$R_{\theta jc}$	0.72	$^\circ\text{C}/\text{W}$
Thermal resistance-junction to ambient	$R_{\theta ja}$	62.5	

7. Electrical characteristics

(T_A=25°C, unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Static characteristics						
Drain-source breakdown voltage	BV _{DSS}	V _{GS} =0V, I _D =250μA	80	-	-	V
Zero gate voltage drain current	I _{DSS}	V _{DS} =64V, V _{GS} =0V	-	-	1	μA
		T _J =125 °C	-	-	100	
Gate threshold voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D =250μA	2	3	4	V
Gate leakage current	I _{GSS}	V _{GS} =±25V, V _{DS} =0V	-	-	±100	nA
Drain-source on-state resistance	R _{DS(on)} ¹	V _{GS} =10V, I _D =40A	-	7.2	9	mΩ
Diode characteristics						
Diode forward voltage	V _{SD} ¹	I _{SD} =40A, V _{GS} =0V	-	0.8	1.5	V
Diode continuous forward current	I _S ³		-	-	80	A
Reverse recovery time	t _{rr}	I _F =40A, di/dt=100A/μs	-	60	-	nS
Reverse recovery charge	Q _{rr}		-	122	-	nC
Dynamic characteristics ²						
Gate resistance	R _G	V _{GS} =0V, V _{DS} =0V, F=1MHz	-	1.6	-	Ω
Input capacitance	C _{iss}	V _{GS} =0V, V _{DS} =25V, F=1.0MHz	-	3650	-	pF
Output capacitance	C _{oss}		-	420	-	
Reverse transfer capacitance	C _{rss}		-	180	-	
Turn-on delay time	t _{d(ON)}	V _{DD} =37.5V, I _D =40A, V _{GS} =10V, R _G =6.8Ω	-	21	-	nS
Turn-on rise time	t _r		-	64	-	
Turn-off delay time	t _{d(OFF)}		-	66	-	
Turn-off fall time	t _f		-	40	-	
Gate charge characteristics ²						
Total gate charge	Q _g	V _{DS} =37.5V, V _{GS} =10V, I _D =40A,	-	75	-	nC
Gate-source charge	Q _{gs}		-	10	-	
Gate-drain charge	Q _{gd}		-	38	-	

Note:1. Pulse test; pulse width ≤300μs, duty cycle ≤2%.

2. Guaranteed by design, not subject to production testing.


3. Package limitation current is 50A. Calculated continuous current based on maximum allowable junction temperature.

4. Repetitive rating, pulse width limited by max junction temperature.


5. Starting T_J=25 °C, L=0.5mH, V_{DD} =50V, I_{AS}=42A.

8. Test circuits and waveforms


Output Characteristics




Drain-Source On Resistance




Drain-Source On Resistance




Gate Threshold Voltage




Drain-Source On Resistance




Source-Drain Diode Forward




Capacitance




Gate Charge




Power Dissipation



Drain Current



Safe Operation Area



Thermal Transient Impedance

